





# **Skytiger ST 30**

## **KEY STRENGHTS**



**CONSTRUCTION QUALITY** 



RADIO-CONTROLLED



**MODULARITY** 



**SAFETY** 

## **MAIN FEATURES**

#### **Technical Features**

Weight - machine body (kg)	790
Dimensions - machine body (mm)	2594 x 997 x 480
Engine	Diesel Turbo - Stage V
Hoisting cable length (m)	100
Hoisting cable diameter (mm)	11
Performance	

Lifting speed (m/s)	Up to 3
Payload single traction (kN)	30

Control System		
	Technology	Radio Control

### **Areas of application**







## **Skytiger ST 30**

### **KEY STRENGHTS**



**CONSTRUCTION QUALITY** 



**RADIO-CONTROLLED** 



**MODULARITY** 



**SAFETY** 

#### SAFETY

Advanced control, braking and rope management systems ensure safe operation

### **EXPANDABILITY**

Compatible with Skytiger 30 NL to increase lifting and horizontal transport capacity

### **BUILD QUALITY**

Sturdy chassis, reliable engine, and high-quality materials ensure durability and long service life

### **VERSATILITY OF USE**

Suitable for various transport types and terrain, ensuring efficient performance in all conditions





# **Skytiger ST 30**



## Why choose the Skytiger 30 NL: All the advantages

- Two independent lifting winches
- ✓ Increased load capacity of the system
- ☑ Reduced maintenance: no engine and hydraulic system on board
- Optimal handling of long loads



### Recommended for:

- Mild line curves
- Quick and delicate crossing of towers





Transport by Rope - design, production, sale and rental of

Seik Srl Via Dolomiti 46 I - 39040 Trodena (BZ) Tel. +39 0471 887 087

E-Mail: info@seik.it

